

TILLAMOOK COUNTY SURVEYORS OFFICE

1/4 corner common to sections 13 & 24 T.2N.,R.10W.,W.M.

S 13
1/4 ---
S 24
1989

I set a 1 1/2" iron pipe with a 3" Tillamook county brass cap in a 10" concrete cylinder at the position of a found axle shaft with gear as reported in Tillamook County Surveyors rewitmess book #2 at page 188. This corner is also the Initial Point of Foley Creek original and Foley Creek 2 subdivisions.

History of found Monument

I found this monument to be as reported on the above said rewitmess and the accessories found and/or set at that time to now be as follows:

"large alder stump" S.55*W. 30 lks. (now gone).

"Large alder stump" N.35*W. 30 lks. (now gone).

20" spruce N.46*W. 21.5'; (now 38" stump 5' high).*

26" hemlock S.22*W. 25.0'; (now 48" hemlock with bark scribing "1/4 S BT" visible). I rescribed 1/4S23BTCS on root flair, distance to nail with CS brass washer in the face is S.26*W. 25.18'.*

Surveys and rewitmesses of reference;

- G.L.O. 2N10 page 21 1873.
- A-2504, John L. Carlich L.S. 287 1973.
- A-2644, Gene Leuthold L.S. 475 1974.
- B-676, Gene Leuthold L.S. 475 1974.
- C-346, Allen & Leuthold Plat of Foley Creek subdivision 1971.
- C-370, Allen & Leuthold Plat of Foley Creek #2 1974.
- B-565, O.S.B.F. L.S. 707 1968
- Book 2 Page 188, W.A. Markham R.E.1842

New Accessories

18" hemlock S.72*W. 28.01' scribed 1/4S24B.TCS distance measured to a nail with a C.S. brass washer in the face.*

84" hat section post North 1.5'.*

*indicates yellow metal Tillamook county corner tag affixed.

Monument Location

This corner is located approximately 50' Southeast of an old alder covered landing on a steep side slope which faces east. I laid the found axle alongside of the new monument.

In the presence of Dan McNutt & Al Dvorak

June 1989

Title Allen E Duncan, C.S.