## TILLAMOOK COUNTY SURVEYORS OFFICE

Initial Point
Nehalem Heights
In Section 27 T.3N.,R.10W..W.M.

INITIAL
POINT
NEHALEM.HEIGHTS
1990

I found a 2" diameter iron pipe 6" deep no plug. I set a 5/8" iron rod with a 3" Tilla-mook County Surveyors brass cap inside of the found iron pipe and encased in a 10" concrete cylinder flush with the surface of ground.

History of Found Monument

The found monument is the original monument set for this initial point, see Tillamook County Surveyors map #C-339. (Also see Tillamook County County Surveyors map #A-3373).

## New Accessories

9" pine S.30\*W. 2.81', the distance was measured to a finish nail with a Tillamook County Surveyors brass washer in a small blaze facing the initial point.

Sewer manhole N.42\*E. 13.21', the distance was measured to a punch mark with an X on the Southwesterly rim.

Location of Monument

This corner is located on the West side of tenth street, South side of a driveway, 1.2' south of a wooden retaining wall.

In the presence of Dan McNutt & Al Dvorak

October 29, 1990

Title:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

allM & Duram, c. s.

OREGON JULY 14, 1967 ALLAN E. DUNCAN 793

NOV 5 1990

CLAVETORS OFFICE