

KEENON LAND SERVICES, INC.

1311 E. ALDER ST.
VERNONIA, OREGON 97064
PHONE 503/429-6115

LAND CORNER RECORD

TILLAMOOK

County

T 3 N, R 6 W, W.M.
Segregated Surveys:

Corner Code No.

Name:


W 1/4, 58

Corner No.:

DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite.

1. History of Corner Establishment and Subsequent Restoration:

1/4 PERPETUATED BY OREGON STATE FORESTRY
IN 1955 WITH STATE PIPE & CAP
A 50" FIR STATE 24 LKS ORIGINAL (NOW STUMP)
12" FIR, S79E, 70'
6" FIR, N31W, 98'



2. Description of Evidence Found:

AFTER REPEATED SEARCH, A STATE I.P. LYING
ON THE GROUND AND THE 50" STUMP WERE LOCATED
PULLING FROM THE ORIG STUMP WE FIND THE 1/4 IN
PLACE, BURIED IN DEBRIS
THE SE BT WITH TAG DATED 1955 IN PLACE AND 28"
THE 6" BT NW NOW A 19" FIR

3. Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location. Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No. Page No. Date of work.

AT THE 1/4 CORNER, SET THE 6 FEET
STEEL POST 10 NORTH,
DROVE A 6" BOLT SPIKE INTO NOTCH AT BASE OF EACH
REFERENCIE BT.
A 28" FIR S79E, 6.20 TO HEAD OF SPIKE
A 19" FIR N37W, 8.75 " " " "
A 16" FIR N72W, 23.7 " " " " IN BOTTOM BASE
A 12" FIR S51W, 16.7 " " " "
THE TWO NEW BT'S MARKED WITH 4 BLAZES (NOTCHES) UP
THE FACE HEAVILY PAINTED, AND A YELLOW LOCATION TAG ON
EACH ABOVE BLAZES.

SURVEYOR'S CERTIFICATE

This corner record correctly represents work performed by me or
under my direction in compliance with the provisions of ORS 209.250,
Laws of 1956, Date

Signature

Certificate No.

BOOK 7 94

