TILLAMOOK COUNTY SURVEYORS OFFICE COURTHOUSE, TILLAMOOK, OREGON 97141

SW CORNER E. TRASK DLC #37, SECTION 33 T.1S., R.9W., W.M.

SW	I found a 1 1/4" iron bar in concrete, (see T.C.S.
E. TRASK	Rewitness #256), 3" deep in the North bound lane of
+	McCormick Loop County Road.
DLC S33	I set a 3" County Surveyors Brass Cap on a 5 /8"
#37	iron rod 12" long in an 8" cast iron monument case
1991	and encased in concrete.

History of found monument

The Tillamook County Surveyors Brass cap set on said Rewitness #256 was ripped off by road maintenance and the references found and/or set at that time are now as follows:

P.U.D. Pole 24.57'; (Found, N.54 W. 24.57'. The new pole number is #331300).

1/2" iron pipe 22.46'; (Found, S.64 W. 22.46').

*86" Hat Section Post West 19.6'; (Found, West 19.53').

 $\mbox{\tt *indicates}$ Tillamook County Surveyors yellow metal location poster attached.

F-40-36 February 1912 G.J. Poysky A-2153 August 1971 John L. Carlich RS 287 A-799 March 1959 John L. Carlich RS 287 A-3290 September 1977 F.M. Gaylord LS 929		Reference surveys n	ot listed on	Rewitness #256	
B-1018 11-13-81 A.E. Duncan LS 793	F-40-36 A-2153 A-799 A-3290 B-789 B-1018	February August March September April 11-13-81	1912 1971 1959	G.J. Poysky John L. Carlich John L. Carlich F.M. Gaylord C.W. Cook A.E. Duncan	AS 287 LS 929 LS 1098

New Accessories

6"X~6" treated fence corner post bears N.48 E. 21.74'. The distance was measured to a finish nail with a brass T.C.S. washer in westerly side of the post.

 $5/8\ensuremath{^{"}}$ iron rod with a yellow plastic T.C.S. random cap bears S.54 E. 21.10'.

Location of Monument

This corner is located in the North bound lane of McCormick Loop County Road, Approximately 2.0' East of the apparent centerline.

In the presence of Al Dvorak and Dan McNutt

July 24, 1991

Title:

SEP 3 1991

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON JULY 14, 1967 ALLAN E. DUNCAN 793

allan & Duncan, c.S.

BOOK 7 98