## TILLAMOOK COUNTY SURVEYORS OFFICE COURT HOUSE. TILLAMOOK OREGON 97141

SECTION CORNER COMMON SECTIONS
10, 11, 14, & 15 T.1S., R.8W., W.M.

T1SR8W I found a 1 1/2" iron pipe with a 3" O. S. B. F. S10|S11 Bronze Cap. (see T.C.S. Rewitness Book 1 at Page --+-- 136). I encased the found iron pipe in a 10" concrete cylinder. 1954
PE 2311

## History of found monument

I found this monument to be as described in Tillamook County Surveyors Rewitness Book 1 at page 136 and the references found and/or set at that time to now be as follows:

(Book 4 Page 38) 24" hemlock N.70°E. 34.8', reported on above rewitness as a 31" stub 30' high with scribes "BT SC" at the same bearing and distance; (Found, now a 25" hemlock stump 3' tall on uphill side, at position, and 0.S.B.F. Yellow Metal Location Poster on the top dated "3-26-53" by "D. Morris, B. Cowen, T. Akers").

\*(Book 1 Page 136)  $\,$  6" alder N.83°W. 50.0 ft.; (Found, now 18" alder, leaning heavily downhill, face healed, I rescribed in the bark "CS BT" N.83°W. 49.62' to a nail with a T.C.S. brass washer between rescribed "B & T").

\*(Book 1 Page 136) 7" alder S.65  $1/2^{\circ}$ W. 44.3 ft.; (Found, now 17" alder, face healed, I rescribed in the bark "CS BT" S.65  $1/2^{\circ}$ W. 43.68' to a nail with a T.C.S. brass washer between rescribed "B & T").

\*(Book 1 Page 136) 6" alder S.41  $1/2^\circ$ E. 48.0 ft.; (Found, now 17" alder, face healed, I rescribed in the bark "CS BT" S.41  $1/2^\circ$ E. 46.85' to a nail with a T.C.S. brass washer between rescribed "B & T").

\*(Book 1 Page 136) 7" spruce N.73°E. 85.3 ft.; (Found, now 16" spruce face healed).

4"X 4"X 60" W.C.P. 1.5' SE of pipe; (Found, rotted off).

 $4"X\ 4"X\ 48"$  white cedar post approximately 660' West of the corner on the East edge of the Trask cut off road; (Now gone) .

Also found a 1/2" iron pipe laying alongside monument.

New Accessory

\*72" light hat section post South 1.0'.

WILLAMOON COLLEGE

IIIN 26 1992

CALEFORS OFFICE

\*indicates Tillamook County Surveyors yellow metal location poster attached.

Surveys and Rewitnesses of record

A-379 W.E. Anderson PE 1697 A-676 Sept. 1956 Arnold G. Gibson RS 359 F-21-29 12-08-36 O.S.H.D. R/W Map Aug. 1968 3-19-54 John L. Carlich **RS 287** Rewitness Book 1 Page 136 Louis M. Amort PE 2311 Rewitness Book 4 Page 38 CS 12-21-31 W.E. Anderson Field notebook 69 page 27-29 & page 123-124 12-21-31 W.E. Anderson CS

Monument Location

This monument is located approximately 100' Southerly of the toe of a steep slope on the steep Northerly slope of a ridge.

In the presence of Dan McNutt and Al Dvorak

May 12, 1992

Title:

PROFESSIONAL LAND SURVEYOR

OREGON
JULY 14. 1967
ALLAN E. DUNCAN
7 9 3

REGISTERED