

REWITNESSED CORNER FOR OREGON DEPARTMENT OF FORESTRY  
4907 Third St., Tillamook, Oregon 97141

One quarter corner common to Sections 7 and 8, T2N, R7W, W.M.,  
Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, August 1, 1893.

18"x13"x10" basalt stone 12" in ground with 1/4 on west face;  
now 10"x8"x6" with 1/4 visible, found out of place.

40" Hemlock bears S40 1/2W 14 lks.; now a 26" badly rotted  
stub with no scribes visible on burnt out face.

40" Fir bears S79E 17 lks.; now a 29"x10 ft. high partly  
uprooted, burnt and rotted stub with no face visible.

REWITNESSED by Louis W. Amort RE2311, November 12, 1953 (Book 2,  
page 311, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 30" in  
ground, on south side of stone, in mound of stone; now  
leaning to NE in proper location for corner point, on west  
edge of small flat.

48" Fir stub 18 ft. high bears N19W 36.2 ft.; now a 3.5 ft.  
high rotted stump with scribes 1/4 S7 BT RE2311 visible.

38" Fir snag bears S21E 25.1 ft.; now a 4 ft. high burnt and  
rotted stump with scribes 1/4 S8 BT visible

4"x4"x48" white painted Cedar post 2.0 ft. North of pipe; in  
place.

REWITNESSED September 28, 1992

Var. 19 1/2 E

From above pipe with marks "LS1998 1992" added a:

15" Fir bears N75E 21.45 ft. to face; scribed 1/4S8BT.

13" Fir bears S06 1/2W 16.7 ft. to face; scribed 1/4S7BT.

Metal location poster on new BTs.

Also 1953 metal location poster on Amort's 48" Fir stub BT.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Placed Original stone on North side of pipe.

Present and witnessed by Clifford R. Foster.

Rewitnessed by David B. Buchholz under my direction.  
David B. Buchholz, ~~SS~~2272

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Anthony J. Klosterman*

OREGON  
JULY 16, 1982  
ANTHONY J. KLOSTERMAN  
1998

