

TILLAMOOK COUNTY SURVEYORS OFFICE  
 201 LAUREL AVENUE  
 TILLAMOOK, OREGON 97141

1/4 CORNER SECTION 1 & 12, T.2N., R.7W., W.M.



I FOUND A 1 1/2' IRON PIPE WITH A 3' D.S.B.F. BRONZE CAP, UP APPROXIMATELY 15', WITH ORIGINAL 14" X 10" X 7" STONE IN MOUND OF STONES SURROUNDING THE IRON PIPE. I ENCASED THE FOUND IRON PIPE AND BRASS CAP IN A MASS OF CONCRETE AND STONES. I PLACED THE ORIGINAL STONE MARKED '1/4' ON THE NORTH SIDE OF THE IRON PIPE MONUMENT.

ACCESSORY EVIDENCE

THIS CORNER WAS FOUND TO BE AS REPORTED IN TILLAMOOK COUNTY SURVEYORS REWITNESS BOOK 5 AT PAGE 336 AND THE ACCESSORIES FOUND OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

(ORIGINAL G.L.D) 24' HEMLOCK S.52°E. 34 LINKS, REPORTED, IN BOOK 5 AT PAGE 336, AS A 36' STUMP FACE BADLY ROTTED; (FOUND, NOW 36' ROTTEN STUMP SCRIBES '1/4' VISIBLE ON THE EDGE OF THE ROTTEN FACE, AT BEARING AND DISTANCE).

(ORIGINAL G.L.D) 34' LARCH N.52°E. 27 LINKS, REPORTED, IN BOOK 5 AT PAGE 336, AS A 24' STUMP FACE BADLY ROTTED; (FOUND, NOW REMAINS OF ROTTEN LARCH STUMP, AT BEARING AND DISTANCE).

(BOOK 2 PAGE 237) 41' NOBLE FIR STUMP N.74°E. 34.0', REPORTED IN BOOK 5 AT PAGE 336 AS A 34' STUMP WITH SCRIBES VISIBLE; (FOUND, ROTTEN NOBLE FIR STUMP, FACE AREA ROTTEN AND FALLEN OFF, AT BEARING AND DISTANCE).

(BOOK 2 PAGE 237) 26' NOBLE FIR STUMP S.26°30'W. 76.3', REPORTED IN BOOK 5 AT PAGE 336 AS A 26' STUMP WITH SCRIBES VISIBLE; (FOUND, ROTTEN NOBLE FIR STUMP, FACE AREA ROTTEN, AT BEARING AND DISTANCE).

(BOOK 5 PAGE 336) 7' NOBLE FIR S.35°E. 3.8'; (FOUND, NOW A 15' NOBLE FIR, FACE HEALED, AT BEARING AND DISTANCE, D.S.B.F. YELLOW METAL LOCATION POSTER ATTACHED).

(BOOK 5 PAGE 336) 7' FIR N.78 1/2°E. 14.5'; (FOUND, NOW A 17' FIR, FACE HEALED, AT BEARING AND DISTANCE).\*

(BOOK 5 PAGE 336) 4' X 4' X 48' WHITE PAINTED CEDAR POST 1.0 FEET SE OF CORNER PIPE ( FOUND, NOW ROTTED OF AND FALLEN OVER).

NEW ACCESSORY

72' LIGHT HAT SECTION POST 1.5 FEET NORTH.\*

\* INDICATES TILLAMOOK COUNTY SURVEYORS YELLOW METAL LOCATION POSTER ATTACHED.

REFERENCES

REWITNESS BOOK 5 PAGE 336	DECEMBER 16, 1974	HAROLD RUSSELL	LS 707
REWITNESS BOOK 2 PAGE 237	DECEMBER 4, 1952	LOUIS AMORT	PE 2311
MAP B-689	MARCH 6, 1975	HAROLD RUSSELL	LS 707

LOCATION OF MONUMENT

THIS CORNER IS LOCATED ±50' SOUTH OF A CAT ROAD AND ± 200' SOUTH OF STANDARD GRADE LOGGING ROAD, (AN OLD RAILROAD LOGGING GRADE).

IN THE PRESENCE OF AL DVORAK AND DAN MCNUTT  
 NOVEMBER 15, 1997


TITLE:

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*Allan E. Duncan, C.S.*

OREGON  
 JULY 14, 1967  
 ALLAN E. DUNCAN  
 793

EXPIRES 12-31-97



BOOK 7 265