

TILLAMOOK COUNTY SURVEYORS OFFICE  
COURTHOUSE, TILLAMOOK, OREGON 97141

SECTION CORNER COMMON TO SECTIONS 36 AND 25, T.2 N.,  
R.10 W. AND SECTIONS 30 AND 31, T.2 N., R.9 W., W. M.

I FOUND AN OREGON STATE BOARD OF FORESTRY IRON PIPE AND BRASS CAP,  
STAMPED AS SHOWN HEREON. I ENCASED THE FOUND MONUMENT IN A 10"  
DIAMETER CONCRETE CYLINDER AND A MOUND OF STONES.

T2N  
R10W | R9W  
S25 S30  
S36 S31  
1968  
RS707

---

HISTORY OF FOUND MONUMENT

THE MONUMENT WAS FOUND AS DESCRIBED ON MAP B-565, AND THE  
ACCESSORIES FOUND AND/OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

MAP B-565, A 32" DIAMETER FIR STUMP BEARING NORTH 89° 30' WEST 21.4'; 08-  
03-05 FOUND A 32" DIAMETER ROTTEN FIR STUMP AT RECORD POSITION, 2.0'  
HIGH, NO MARKS VISIBLE.

MAP B-565, A 24" HEMLOCK STUMP BEARING NORTH 75° 30' EAST 51.1'; 08-03-05  
FOUND A 24" DIAMETER ROTTEN SHELL AT RECORD POSITION, 4.0' HIGH, NO  
MARKS VISIBLE.

MAP B-565, A 30" DIAMETER FIR STUMP BEARING SOUTH 7° 45' WEST 10.3'; 08-03-  
05 FOUND A 30" DIAMETER ROTTEN FIR STUMP AT RECORD POSITION, 4.0'  
HIGH, NO MARKS VISIBLE.

MAP B-565, A 55" DIAMETER FIR SNAG BEARING SOUTH 77° 30' EAST 30.5'; 08-03-  
05 FOUND A 55" DIAMETER FIR SNAG WITH RUSTY TAG, SCRIBING VISIBLE, AT  
RECORD POSITION, 6.0' HIGH, NO MARKS VISIBLE.

MAP B-565, SET A 4" X 4" X 60" WHITE CEDAR POST 1.0' SE OF CORNER PIPE. 08-  
03-05 FOUND A ROTTEN WHITE CEDAR POST LYING NEXT TO MONUMENT.

MAP B-565, FOUND 1" IRON PIPE BEARING SOUTH 71° 52' 30" EAST 26.38'; 08-03-05  
FOUND BADLY RUSTED 1" IRON PIPE, 0.40' ABOVE THE GROUND, SLIGHTLY  
LEANING TO THE SOUTHWEST, AT RECORD POSITION.

---

SURVEYS AND REWITNESSES OF RECORD

B-389	1958	JOHN L. CARLICH	LS 287
A-1208	OCTOBER 1964	JOHN L. CARLICH	LS 287
B-565	JULY 1968	HAROLD J. RUSSEL	LS707
B-763	JUNE 23, 1977	HAROLD J. RUSSEL	LS707

G.L.O. ORIGINAL ON BLM MICROFILM VOLUME R122 AND TRANSCRIBED IN  
G.L.O. BOOK 1, PAGE 14, TILLAMOOK COUNTY SURVEY RECORDS.

NEW ACCESSORIES

29" DIAMETER HEMLOCK BEARING SOUTH 15° EAST 66.25' SCRIBED  
"T2NR9WS31BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED  
"T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

\*14" DIAMETER ALDER BEARING NORTH 62° WEST 18.60' SCRIBED  
"T2NR10WS25CSBT". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED  
"T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

\*15" DIAMETER FIR BEARING SOUTH 35° WEST 36.8' SCRIBED  
"T2NR10WS36BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED  
"T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

\*6" DIAMETER SPRUCE BEARING NORTH 33° EAST 16.62' SCRIBED  
"T2NR9WS30BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED  
"T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

\*SET 72" LIGHT HAT SECTION POST SOUTH 3.0'

\* INDICATES TILLAMOOK COUNTY YELLOW METAL LOCATION POSTER  
ATTACHED

---

LOCATION OF MONUMENT

THIS SECTION CORNER IS LOCATED SOUTH 30° EAST +/- 62' MEASURED ON  
SLOPE FROM AN ALDER WITH A TILLAMOOK COUNTY YELLOW METAL  
LOCATION POSTER ON NORTH FACE OF THE TREE ALONG THE SOUTH SIDE OF  
AN EXISTING GRAVEL ROAD.


NOTE: NO ATTEMPT WAS MADE TO VERIFY THE POSITION OF THIS MOMUMENT  
FROM THE INFORMATION CONTAINED ON MAP B-565. THE INTENT OF THIS  
REWITNESS/RESTORATION IS TO PERPETUATE THE POSITION AS ESTABLISHED  
BY MAP B-565.

IN THE PRESENCE OF, AND REWITNESSED BY DANNY R. MCNUTT, TILLAMOOK  
COUNTY SURVEYOR AND JOE JENSEN, SURVEY SUPERVISOR, TILLAMOOK  
COUNTY SURVEYOR'S OFFICE.


---

AUGUST 03, 2005

TITLE:



*Danny R. McNutt*



RENEWAL12-31-06