

LINCOLN COUNTY CORNER REPORT
NORTHWEST CORNER OF SECTION 19, (06-09)
GCDB 0609102398
LINCOLN COUNTY GEODETIC CONTROL STATION 63COR
SHEET 1 OF 1

1904 MORRIS WYGANT GLO CONTRACT 758

SET: HEMLOCK POST, 3' LONG, 4" SQUARE, 24" IN THE GROUND, FOR CLOSING CORNER OF SECTIONS 24 (T6S R10W) AND 19 (T6S R9W), MARKED "CC ON SOUTH, "T6S R9W S19" ON EAST, AND "T6S R10W S24" ON WEST FACES, WITH 3 GROOVES ON SOUTH AND NORTH FACES, FROM WHICH:
FOUND:

- CORNER OF SECTIONS 18 (T6S R9W) AND 13 (T6S R10W), WHICH IS A POST FIRMLY SET, AND MARKED AND WITNESSED AS DESCRIBED BY THE SURVEYOR GENERAL, BEARS S 89°56' W, 154 LINKS (101.6').

NEW:

- 30" HEMLOCK MARKED "T6S R9W S19 BT" BEARS S 23°30' E, 14 LINKS (9.2').
- 12" HEMLOCK MARKED "T6S R10W S24 BT" BEARS S 85° W, 21 LINKS (13.8").
- A CABIN BEARS S 83° E, 5 CHAINS (330').

1984 JAMES W. PROCHNAU CS 10649

FOUND: NO EVIDENCE OF CORNER.

SET: 2 X 30" GALVANIZED IRON PIPE WITH 2-1/2" BRASS CAP BY SINGLE PROPORTION BETWEEN ORIGINAL S.I.R. 46-1/2 MILE CORNER AND PROPORTIONED CORNER OF SECTIONS 13 (T6S R10W) AND 18 (T6S R9W), MEASURED S 88°21'43" E, 1104.82' (GLO EAST, 17.43 CHAINS = 1150.4') FROM WHICH:

NEW:

- 10" HEMLOCK SCRIBED "T6S R9W CC S19 BT" BEARS S 47° E, 15.7'.
- 12" HEMLOCK SCRIBED "T6S R9W CC S24 BT" BEARS S 78° W, 22.4'.
- STANDARD CORNER OF SECTIONS 13 (T6S R10W) AND 18 (T6S R9W), 2" GALVANIZED IRON PIPE AND 2-1/2" BRASS CAP BEARS N 88°21'43" W, 99.56' (GLO S 89°56' W, 101.6').

1987 NORMAN D. SPRINGER CS 11767

FOUND: 2" IRON PIPE WITH 2-1/2" BRASS CAP MARKED "T6S R9W S18/S24/S19 CC 1984 PLS 1305", (CS 10649), FROM WHICH:

- 10" HEMLOCK WITH SCRIBING VISIBLE, BEARS S 47° E, 15.7'.
- 12" HEMLOCK WITH SCRIBING VISIBLE, BEARS S 78° W, 22.4'.
- 2 IRON PIPE WITH 2-1/2" BRASS CAP MARKED "T6S R10W R9W S13/S18/ 1984 PLS 1305" BEARS N 88°21'35" W, 99.53' (CS 10649 N 88°21'43" W, 99.56').

2008 LINCOLN COUNTY SURVEYOR'S OFFICE

FOUND: 2-1/2" OUTSIDE DIAMETER GALVANIZED IRON PIPE 0.6' ABOVE GRADE WITH 2-1/2" BRASS CAP MARKED "T6S R9W S18/S24/S19 CC 1984 PLS 1305", FROM WHICH:

- NO EVIDENCE OR ORIGINAL BEARING TREES OR CABIN.
- 12" HEMLOCK STUMP 6' TALL WITH SHEET METAL CAP AND HEALED BLAZE, PLUS BEARING TREE TAG MARKED "N 47° W, 15.7'" AND AN ATTENTION SIGN ON THE BACK BEARS S 47° E, 15.7' (= CS10649).
- 19" HEMLOCK WITH HEALED BLAZE AND ILLEGIBLE ALUMINUM LOCATOR TAG, PLUS AN ATTENTION SIGN ON THE BACK, BEARS S 78° W, 22.4' (= CS 10649).
- 2-1/2" OUTSIDE DIAMETER GALVANIZED IRON PIPE 0.9' ABOVE GRADE WITH 2-1/2" BRASS CAP MARKED "T6S R10W R9W S13/S18 1984 PLS 1305" BEARS N 88°19'29" W, 99.56' (CS 10649 N 88°21'43" W, 99.56)
- STEEL T-POST BEARS NORTH, 3.4'.
- CARSONITE POST FACING SOUTH BEARS EAST, 2.5'.
- BLAZED TREE LINE EXTENDS SOUTHERLY ALONG EAST EDGE OF STANDING TIMBER.

NEW:


- 5/8" X 30" IRON ROD AT GRADE WITH 2" LINCOLN COUNTY ALUMINUM CAP MARKED "63AZ 2008" BEARS S 25°35'20" E, 248.24'. A CARSONITE POST IS 3' NORTH.

CONCLUSION: THE PIPE FOUND IS THAT SET BY PROCHNAU IN 1984.


MEASUREMENTS WERE DONE WITH A LEICA TCA1105 TOTAL STATION, POCKET COMPASS AND STEEL TAPE. BEARINGS ARE GEODETIC, BASED UPON STARNET PROJECT 6-9.PRJ AND THE MAPPING ANGLE OF -2°22'17" AT THE SECTION CORNER.

WITNESSES: PHIL LAMBERSON

LINCOLN COUNTY SURVEYOR'S OFFICE
880 NE 7TH ST.
NEWPORT, OREGON 97365
(541)-265-4147



Tom Hamilton



RENEWAL DATE: JUNE 30, 2009