

T65 R. 10W.	R.D. 11C B.O.	County TILLAMOOK	USFS File #
WILL.	N.F. SILUSLAW	State ORE.	J-23
AGRAM J-23	DESCRIBE CORNER MONUMENT FOUND GLO 1890 SET Post & MKD, 24" HEM., S. 77½° W., 57 LKS. 24" HEM., N. 77½° E., 56 LKS.		
12	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND. BY RECORD J. S. FORREST, SPAULDING PULP AND PAPER CO., WAS DEPUTIZED YEAR 1950, BY TILLA. CO. SURVEYOR, W.E. ANDERSON TO RE-WITNESS THIS CORNER. FROM THE REMAINING BT A 24" HEM. N. 77½° E., 56 LKS. WITH VISIBLE SCRIBE MARKS "¼ SBT."		
13			
VERIFICATION DATA	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER FORREST SET 1½" IRON PIPE 5 FT. LONG 2 FT. IN GROUND FROM WHICH HE SCRIBED 2 NEW WITNESSES: 1" HEM., S. 16° W., 70 FT. SCRIBED "¼ SBT." 2" HEM., N. 72° W., 55 FT. SCRIBED "¼ SBT."		
DATE POSITION DATA			
TIME			
ENT ID 30			

COMMENTS:

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT FOUND 1½" PIPE SET BY FORREST 1950 BENT OVER. I SET ½" IRON ROD AT CORNER POINT. <i>Second reference is a Deputy County Surveyor, temporary & re-witness a positive identifiable found monument in connection with his USFS work J.L. Carlin, CS 12/74.</i>			
ACCESSORIES: DESCRIBE NEW BT & WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVI I MARK 2 NEW BT: 9" HEMLOCK, N. 19° W., 8½ FT. SCRIBED "¼ S 12 CSBT." 10" FIR, S. 83° E., 19½ FT. SCRIBED "¼ S 13 CSBT."			
Leonard Whitmore, Tilla. County Dep. Surveyor. 2-16-73			
Work Done By	Title	Date	State Registration No. or Agency
Certified Cor. Record Prepared?	Yes	No	Filed At
REMARKS			Date
CORNER IS LOCATED 125 FT. WEST OF A ROCK ROAD NEAR A PROPERTY BOUNDARY E.N. NORTH AND WEST OF THE COR. T65 R10W 14 COR 12			

REWITNESS